



A	2020.12.20	All	AOS-AONS36302		

V

V

BRCS016N03ZC

Rev.A Dec.-2021




DATA SHEET

# \$ Parameter	% & Symbol	\$ ' Rating	() Unit
Drain-Source Voltage Drain	V_{DS}	30	V


/ Electrical Characteristics(Ta=25)

# \$ Parameter	% & Symbol	* + , - Test Conditions	. / ' Min	0 1 ' Typ	. 2 ' Max	() Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=15V$ $R_L=0.75\ \Omega$ $R_{GEN}=3\ \Omega$		12.5		ns
Turn-On Rise Time	t_r			6.0		
Turn-Off Delay Time	$t_{d(off)}$			47		
Turn-Off Fall Time	t_f			10.5		

/ Electrical Characteristic Curve




/ Electrical Characteristic Curve



/ Package Dimensions


PDFN5 X6

Unit:mm



Rev.00x201812

/ Marking Instructions



! " 3

BR 3 4 5 6 7 8

016N03 3 4 1 & 7 8

**** 3 4 9 : ; & 7 8 < = 9 : ; & > ?


Note:

BR: Company Code.

016N03: Product Type Code.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180°C, Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5°C, Duration:5±0.5sec. |
| 3 | | 2 | 10°C/sec. | | 3. Cooling Speed: 2~10°C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5°C 10±1 sec. Temp.:260±5°C Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box 盒	Outer Box 箱
PDFN5 × 6	5000	2	10000	6	60000	13" × 12	360 × 360 × 50	380 × 335 × 366

/ Notices